

MULTIWAY CONNECTORS

A range of popular and inexpensive non-environmentally sealed connectors for general purpose applications that aren't exposed to the elements. Each circuit is rated to 20A. Derating factors may apply for multiple circuits. The gender of a housing is determined by the housing alone - not the type of terminal it accepts. Some series of housings can accept both male & female terminals (reverse gender), so using this methodology saves confusion when ordering. Material is black Nylon66 with a maximum service temperature rating of 106°C - higher than standard automotive cables.



21511
1 circuit
male housing



21501
1 circuit
female housing



215112
1 circuit male housing suit
sender units with a slide-on
button terminal.



21512
2 circuit male
'tee' housing



21502
2 circuit female
'tee' housing



56209
Female locking terminal
suit 21511 & 215112 housings.
Quality tinned brass material.
For cable up to 4mm auto.




21513
3 circuit
male housing



21503
3 circuit
female housing



21500
Female locking terminal
suit all male housings except
21511 & 215112 (use 56210)
Quality tinned brass material.
For cable up to 4mm auto.




21514
4 circuit
male housing



21504
4 circuit
female housing

215001

As 21500 but for 5mm auto cable.




21516
6 circuit
male housing



21506
6 circuit
female housing



21510
Male locking terminal suit
all female housings.
Quality tinned brass material.
For up to 4mm auto cable



21518
8 circuit
male housing



21508
8 circuit
female housing

215101

As 21510 but for 5mm auto cable

**STOCK BOX AVAILABLE.
SEE OUR KITS SECTION
FOR MORE DETAILS**